

Proposal

Biogas plant
electric power 6900 kW
using 100% maiz



Date: 11/04/2024

Validity: %1/01/2025



CONTENTS

Overview	3
Raw material potential	4
Biogas plant technical performances	5
Working principle	6
Technological process of biogas production	7
Main equipment	8
Loader	9
Digester	10
Window with spotlight	11
Digester vertical mixer	12
Pump equipment	13
Separator	14
Submersible mixer	15
Gasholder	16
Biogas dryer and cooling	17
Biogas compressor	18
Desulphurization system	19
Flare	20
Cogeneration power plant	21
Gas analyzer (CH ₄ , CO ₂ , H ₂ S, O ₂)	22
Heating system	23
Water supplying and sewerage system	24
Air supply system	25
Dry cooler (digester cooling)	25
Automation and electrical equipment	26
Sensors set	27
Specification list	28
Appendices	33
Appendix 1 Material Flow diagram	34
Appendix 2 Basic diagram	35
Appendix 3 Plan Layout	36
Appendix 4 Electric power consumption	37
Appendix 5 Price equipment (Detailed)	38
Appendix 6 Price	39



OVERVIEW

We offer a solution to process maize silage into biogas in high-load reactors (HLR). The proposed HLR technology is superior to the conventional CSTR. HLR is 3 times smaller and cheaper than CSTR. To produce 6,9MW using maize just 3 HLR x 3776 m³ are enough.

Raw material potential

Substrate	Quantity (tonnes/day)	Quantity (tonnes/year)	DM content: (%)	ODM content (%)	DM quantity (tonnes/ day)	ODM quantity (tonnes / day)	Biogas yield (m ³ / tonneODM)	Biogas (m ³ /day)	Methane content (%)	Biogas (m ³ /year)
Maize silage	324	118 260	36	94.8	116.6	110.6	670	74 080	52	27 040 295

Biogas plant technical performances

Characteristics	Values	Figures
Number of digesters	units	3
Digester		
a) volume:		
Work	m ³	3 433
Overall	m ³	3 776
b) Organic load	kgODM/ m ³	10,76
c) Hydraulic retention time (gross)	days	35
d) Overall dimensions of the digester (diameter / height)	m	27,0/6,6
e) Temperature	°C	+48
Gasholder		
a) Volume	m ³	800
b) Number of gasholders	units	1
c) Dimensions of the gasholder (diameter / height)	m	12,6/9,7



WORKING PRINCIPLE

Biogas plant working principle

The technology is based on the biochemical conversion of organic materials from high molecular weight compounds to low molecular weight compounds. The first stage of this process is hydrolysis. Hydrolysis produces organic acids and alcohols.

Organic compounds + H₂O → C₅H₇N₀2 + HCO₃.

Further conversion of obtained dissolved compounds like organic acids and alcohols (C₅H₇N₀2, HCO₃) into gases - CH₄, CO₂. C₅H₇N₀2 + HCO₃ + H₂O → CH₄ + CO₂ + NH₄.

Biological process of consecutive (phasic) conversion of organic compounds take place in anaerobic environment i.e. in oxygen-free tank (biological reactor). At the first stage of fermentation, substrate hydrolysis take place under acidogenic bacteria influence. At the second stage, elementary organic compounds come through hydrolysis oxidation by means of hetero-acidogenic bacteria with production of acetate, carbon diox-

ide, and free hydrogen. The other part of the organic compound including acetate forms C₁ compounds (elementary organic acids). Produced substances are the feedstock for methanogenic bacteria of the third type. This stage flows in two processes of A and B type the character which depends on caused by different bacteria type. These two types of bacteria convert the compound obtained during the first and second stages into methane CH₄, water H₂O and carbon dioxide CO₂. Methanogenic bacteria are more sensitive to the living environment compared to acidogenic bacteria. They require a complete anaerobic environment and a longer reproduction period. The speed and scale of anaerobic fermentation depends on bacteria metabolic activity. That is why the biogas plant chemical process includes hydrolysis stage, oxidation, and methanization stage. For that kind of substrate, these processes take place in the same reactor

Technological process of biogas production

Maize silage is transported to the biogas plant area and discharged into a loader. The loader is equipped with a moving floor. The supply of raw materials is carried out by screws into the digesters evenly throughout the day. In the high-load digesters the substrate is brought up to a temperature of +48 °C. Constant temperature is sustained for the entire digesting period. The digester operating regime is thermophilic. The heated substrate in the digester is blended periodically by vertical agitators. The average time of processing in the digesters is 35 days (gross).

After the digesters, the substrate is fed by the pumps to the separator area where it is separated into solid and liquid bio-fertilizer. Solid bio-fertilizer is discharged to the separation area and transported for storage; liquid filtrate is directed to a filtrate tank and then to a lagoon. Biogas plant is equipped with gasholder for accumulating of biogas. The gas holder's weather protective film protects the gasholder from precipitation and damage by foreign objects. The weather protective film is fixed firmly by a special system. To protect the gasholder from overpressure, digesters are equipped with safety valves, which starts working at a pressure of 5 mbars

and bleeds biogas to the atmosphere.

The biogas then goes through a gas pipeline to a compressor, where the pressure is raised up to 80-150 mbar to meet engine requirements. After the compressor, biogas is supplied to a cogeneration power plant, where biogas is used as fuel for production of electricity and heat energy in the same time.

All technological processes are controlled and operated by an automatic system. Biogas plant work is monitored at the central control room monitor. The control room is equipped with a central control unit, which allows the switching of any biogas plant module into automatic or manual mode with local or remote control.

MAIN EQUIPMENT





Solid feeder

Solid feeder machines have been proven in various situations. Solid feeder has the solid design, which guarantees a maximum functionality and less maintenance, combined to a low energy consumption. Because of the vertically oriented walls, there is no change for the material to get stuck or build bridges. The conveyor chains and the milling-unit allow continuous dosing by various types of materials. Furthermore, the material is loosened by this dosing process. The user is able to control the material flow up to 20m³/h or more, regarding to the own consumption of electrical power by the machine. In addition, the corrosion protection, wear resistance and high quality allow customers to use our product for a long period of time.

Specifications

Length:	13,8 m
Width:	2,5 m
Height:	3,6 m
Volume:	50 m ³
Quantity:	3 pcs.



Digesters

Digester is a tank of cylindrical form (for better mixing during the fermentation). It is built of cast-in-situ reinforced concrete based on sulphate-resistant cement with thickness of walls and bottom - 0,25m. In the center of the digester there is a column with chapter. Overlap of digester is reinforced concrete plate. On the tank's wall and in the bottom there is to be installed pipelines for heating, intended for assurance and maintenance of the optimal fermentation process temperature at thermophilic conditions. For heat conservation and reduction of heat energy con-

sumption, the digester walls, overlap and bottom are insulated outside with 100 mm slabs of extruded polystyrene foam. Over the heater, the substructure walls and bottom are insulated with roll damp proofing. Superstructure and substructure heat insulation is protected by shaped sheet from the outside mechanical damages and rodents. The digester bottom has a slope 1%.

Specifications

Height:	6,6 m
Diameter:	27,0 m
Overall volume:	3776 m ³
Quantity:	3 pcs



Window with spotlight

Inspection windows are designed for visual control of processes inside the fermenter and post-digester. Spotlights were made in explosion-proof with automatic disconnec-

tion. Inspection windows are equipped with a cleaning washing system.

Specifications

Inspection windows Ø300
Spotlight VISULUX UL50 -G -H
230V, 50W, IP65



Digester vertical mixer


Mixers are designed and engineered to guarantee high energy efficiency. We use gear units and motors from respected European manufacturers.

This guarantees the long life of our mixers. All motors and gear units are available with ATEX certifications.

Agitators are designed for mixing substrates with a high solids content of 13-18%. The blades of the mixers are set at an optimum angle, and the external motor of the mixer is mounted on a special support.

Specifications

Nominal power	N=15 kW
Quantity per digester:	6 pcs
Quantity total:	18 pcs



Pump equipment

Pumps are used to transport substrate to the equipment and facilities in the biogas plant and away. Kinematic viscosity is a real physical factor that influences pump curves, and thus the choice of pump. Viscosity is essentially resistance to flow and this has implications for pumps. Fluid viscosity or thickness will affect how it will behave in a pump. Screw pumps are used for pumping flowable thin sludge, - excess sludge and mechanically thickened sludge and conveying the substrates with their mostly high dry substance contents (DS) containing up to 10% dry matter. Optimum pumping results are guaranteed by the flow-optimized suction housing and a constant joint diameter which prevents the plaiting of long fibers.

Specifications

Substrate feed pump

Flow rate:	30 m ³ /hour
Engine power:	11 kW
Pressure:	4 bar
Quantity:	1 pcs

Substrate pump to separator

Flow rate:	30 m ³ /hour
Engine power:	11 kW
Pressure:	4 bar
Quantity:	3 pcs

Filtrate pump

Flow rate:	30 m ³ /hour
Engine power:	11 kW
Pressure:	4 bar
Quantity:	1 pcs



Separator

Separator separates water from solids. It operates continuously and automatically according to the press screw separator principle and separates thin and viscous compounds. Solid matter / liquid compound is pumped from the inlet chamber by the press screw into the horizontal screen. Some of the water flows due to the force of gravity through the screen. Press screw conveys the rest of the water with solid particles (also smallest particles) into the press zone in the last section of the screen. Here a permanent regenerative, compact solid matter is generated and is then pressed out through the outlet of the machine, which can be easily filled into containers. Separated fluid flows through outlet underneath the machine. On the grounds of narrow tolerance the inside of the screen is permanently kept clean.

Specifications

Engine power	5,5 kW
Flow rate	up to 30 m³ / h
Quantity	3 pcs
Equipment	
Frame	
Screw	
Sieve for the filtration	
Counterweights	
The design of the protective room	



Submersible mixer

The submersible motor agitator serves for mixing renewable raw materials (RRM), liquid substrate as manure, poultry dung and similar substrates. The electro-motor driven submersible agitator is designed for submersion operations in potentially explosive environments of Ex zone 2 and complies with Directive 94/9 EC. The submersible agitator can be attached to most sliding masts by means of the motor support. A mounting option for a hauling cable is provided on the motor support for height adjustment purposes.

Due to the 4-roller guidance of the motor support, the agitator can be lifted and lowered without friction and the square mast, even if the pull of the hauling cable is slightly angular. The motor support is designed for a 100 x 100 mm square sliding mast as standard, but can also be used for an 80 x 80 mm sliding mast by changing the

rollers. The strain relief of the connecting cable can be positioned in the extension of the motor or towards the top on the motor support, depending on the requirements. This enables universal utilization with the most various installation kits.

The geared motor is made of spheroidal graphite iron (GGG40) and painted, the propeller is galvanized and the motor support is made of stainless steel. The submersible motor agitator is designed as a water pressure-tight monoblock unit for driving the three-vane propeller. The submersible agitator is of modular design, submersible electro-motor with flange-mounted planetary gear and bearing flange for holding the propeller. The conical shaft in the bearing flange is mounted in the oil bath by two angular roller bearings and sealed off from the agitating substrate with a mechanical seal.

Specifications

Filtrate tank

Nominal power

Quantity:

N= 3,0 kW

1 pcs

Height:

adapted to the height of digester

Material: stainless steel 8 mm



Gasholder

The gasholder provides for biogas storage and for equalizing pressure and biogas composition. The gasholder system has a two-layer construction. The external material consists of a weather-proof film of PVC-coated polyester fabrics with UV protection. Both sides are finished with an external N/5cm, internal membrane PEELD (gasholder) membrane.

The gasholder has a methane permeation maximum of $260 \text{ cm}^3/\text{m}^2 * 1 \text{ bar}$ biogas resistance. The gasholder film temperature range allows operation from -30°C to $+60^\circ\text{C}$.


The internal film is stretched under normal biogas pressure. Air is blown into the space between the external and internal membranes to pressurize the internal membrane and form the shape of the external membrane.

The biogas pressure in the gasholder is 2-5 mbar. The membranes are designed and cut out on NC machines. Welding is executed by high frequency currents. These steps yield substantial improvements for quality and service life compared to hand-made membranes welded by standard welding equipment.

To prevent damage to the gasholder as a result of overpressure conditions, a safety valve is installed. To survey the internal membrane, an inspection window is installed on the external membrane.

Specifications

Height :	9,7 m
Diameter :	12,6 m
The total volume :	800 m ³
Quantity:	1 pcs



Biogas dryer and cooling

Biogas dryer and cooling are provided with special equipment as GAS COOLER and AIR-COOLED LIQUID CHILLER. Biogas plants thanks to an extensive range of dedicated Biogas solutions, low pressure heat exchangers, a comprehensive range of water chillers and RWD Dry Coolers. Designed as one-way shell-and-tube heat exchanger. Process gas inside of the tubes; cooling water in the shell. All parts in contact with the process gas made of stainless steel 316Ti or 316L; heat exchanger shell made of stainless steel/ Designed with gas outlet chamber outlet connection radial; inspection opening axial Official acceptance according to PED 2014/68/EU in accordance with ADMerkblätter and factory pressure test.

Specifications

Gas volume flow	1600 m ³ / h
Gas inlet temperature	+48 C
Gas outlet temperature	+10 C
Engine power	75 kW
Quantity	2 pcs



Biogas compressor

Biogas blower is a device used to move gas and increase pressure thanks to a rotating impeller within a toroidal channel, so there is a progressive increase of energy. Blower is used to transporting biogas from gasholder storage to consumer.

Specifications

Flow rate	3100 m ³ /h
Pressure	150 mbar
Engine	36,0 kW
Quantity	1 pcs



Desulphurization system

The desulphurization system is a one-step purification of biogas to remove sulfur. The system cleans biogas of sulfur using activated charcoal filtration, as activated charcoal has the capability to absorb sulfur. After passing through activated charcoal filters, the sulfur concentration is reduced to 0 ppm.

Specifications

The volume of charcoal

3 000 kg

Numbers of charcoal columns

3 pcs



Flare

The flare is designed for the temporary or periodical complete combustion of the biogas produced by biogas plants without the possibility of its use as an energy source. The burn system consists of a burner and additional equipment. The burner is designed on the principle of injection and consists of a combustion nozzle with an injector with an air supply control system, flame protection tube, fitting and burner control system. The biogas combustion system is made of stainless steel.

The supporting structure holds the burner and vertically mounted socket. The burn control system is installed in a case, which is mounted on the supporting structure of the combustion system and contains all the elements for monitoring and controlling ignition and flame.

Specifications

Flow rate

31 00 m³/h

Quantity:

1 pcs



Cogeneration Power Plant

A cogeneration power plant (CHP) is used for producing electricity and heat. CHP is a very efficient technology for generating electricity and heat together. A CHP plant is an installation where there is simultaneous generation of usable electric power and heat in a single process, and it can provide a secure and highly efficient method of generating electricity and heat at the point of use. Due to the utilization of heat from electricity generation and the avoidance of transmission losses, due to electricity being generated on site, CHP typically achieves a 35 per cent reduction in primary energy usage compared with power stations and heat only boilers. This allows for economic savings where there is a suitable balance between heat and power loads. Another important factor, showing the benefits of cogeneration and CHP, is its low environmental impact. CHP produces lower quantities of pollutant emissions and heat pollution of the atmosphere. The current mix of CHP installations achieves a reduction of over 10 per cent in CO₂ emissions in comparison with combined-cycle gas turbines.

Specifications

Produced electric power	2300 kW
Produced heat power	2165 kW
Emissions	NO _x < 500 mg/Nm ³ (5% O ₂)
Generator	400V, 50Hz

Quantity: 3 pcs



Gas analyzer (CH₄, CO₂, H₂S, O₂) (GA-01)

Gas analyzer - a measuring device to determine the qualitative and quantitative composition of the gas mixture. In a biogas plant's installed absorption gas analyzers, biogas mixture components are absorbed sequentially with various reagents. Automatic gas analyzers continuously measure any physical or physicochemical characteristics of the gas mixture or its individual components. Operation is based on physical methods of analysis, including auxiliary chemical reactions.

Specifications

Set includes

- Device for wall mounting
- LCD display menu
- Flow meter / control valve
- Sensors

Defined gases methane % (CH₄), carbon dioxide % (CO₂), hydrogen sulfide ppm (H₂S)



Heating system

Heating equipment is used for biogas plant heating and for sustaining constant temperature in the fermenter. Heating equipment includes circulation pumps, heat exchanger, heating manifold and pipes. The heat from the boiler is transferred to the biogas plant by using heat exchanger, and then is pumped through of biogas plant by circulation pumps. A heat carrier prepares water with an additive of ethylene glycol. Inlet temperature in the fermenter is 60C, the outlet is 40C.

Specifications

Circulation pump for supplying network water and electric boiler		Circulation pump for mains supply to the digester	
Flow	7,8m ³ /h, ,	Flow	11 m ³ / h;
Pressure	6 m	Pressure	10m
Electric power	0,37 kW;	Electric power	0,75 kW;
Circulation pump of heat carrier		Diaphragm expansion tank with volume V = 500L	
Flow rate	0,4 m ³ / h;		
Pressure	0,3m		
Electric power	0,04 kW;	Propylene glycol storage tank with volume V = 300L with overflow line and float shut-off valve	
Circulation pump for supplying heat carrier to CHP		Electric hot water boiler with temperature limiter and safety valve	
Flow	31 m ³ / h;		
Pressure	8 m ,		
Electric power	1,5 kW;	Electric hot water boiler with temperature limiter and safety valve	
The pumping station feeding propylene glycol			
Flow	1,0 m ³ /h;		
Pressure	4 bar,		



Dry cooler (digester cooling)

The device is designed to cool the reactor. When using highly loaded technology, there is a chance of uncontrolled self-heating.

The cooler is connected to the heating pipes, and when active, the same lines are used.

Specifications

Power	100 kW
Engine power	4,0 kW
Quantity:	3 pcs

Water supplying and sewerage system

Water supplying system provides biogas plant feed water, water for network circuits, the domestic water and fire safety systems. As used centrifugal single stage pumps as main pumping elements. These pumps are designed for pumping waste water, household / domestic water and sewage. Pressure Boosting Systems are designed for pure water pressure boosting in industrial plants. The booster comprises 2 to 3 (connected in parallel pumps) installed on a common base frame, and provided with all the necessary fittings.

Specifications

Water supply pump station (drinking water)

Pressure 28 m

Flow 9 m³ / h

Engine 0,75 kW

Water fire extinguishing pump station

Pressure 28 m

Flow 51 m³ / h

Engine 7.5 kW

Drain pump

Pressure 5 m

Flow 4.5 m³ / h

Engine 0.37 kW

Equipment

Pump case control

Stove-base

gauges

Air supply system

Air supply system ensures retention of the protective dome digester. This is achieved by installing a pneumatic lock and maintain the required pressure therein.


Specifications

Flow rate 200l/min

Max. Pressure 8Bar

Speed 2850 rev/min

Receiver capacity 9,5l



Automation and electrical equipment

Process control equipment is used for supervision and regulation operation of the plant and for the limitation of damage. In case of emergency (for example, breakdown of the electrical power supply) the biogas plant is automatically transferred to safe operating conditions by the process instrumentation. Critical electrically driven devices are supplied with emergency power. An automatic system allows the supervision of the plant in real time and to recognize and correct aberrations immediately; to run the plant at its optimum saving resources and costs; and to record for the electronic database operation parameters. The automatic system consists of a control cabinet and sensors for parameter control of technological processes and execution devices.

The control cabinet is designed based on the industrial controller Siemens CPU315-DP2, using periphery distributing system Simatic ET200S, and operator panel OP277 Touch with touch-sensitive controls. Communications is executed by PROFIBUS and MPI with physical interface RS-485. The control program is designed based on the Simatic Step7. The control cabinet is a modular design. The upper part has a power box with central and front-end processor. The periphery distributing system, Simatic ET200S, is installed with input - output units. The lower part with interface relay and clips is installed for connecting execution devices. The entire plant is controlled by a single operator.

Specifications

Incoming control case with automatic set ASE-1, 2, 3
Base Siemens CPU315-DP2 controller
Peripherals Simatic ET200S
Control panel OP277 touchscreen
Communication PROFIBUS and MPI
Interface RS-485
Control system Simatic Step7



Sensors

Sensors are used to measure physical quantities (temperature, pressure, level of moisture) data collection.
installation kits

Specifications

Conductometric sensor
Pressure Sensor / level
Ultrasonic sensor
Gas Pressure Sensor
Temperature converters with protective sleeves
The moisture sensor and the gas temperature

SPECIFICATION LIST



Nº	Equipment	Characteristic	Q-ty
2	Loader	N=50 m3	3
2.1	Container bunker		3
2.2	Feeding screws	set.	3
3	Vertical mixer (digester)	N=15,0 kW	18
3.1	Airtight motor gearbox		18
3.2	Hydraulic screw (wear-resistant steel)		18
3.3	Mixer control mechanism (high-quality structural galvanized steel)		18
3.4	Electric motor mount (high-quality structural galvanized steel)		18
3.5	Set of fasteners (coating - hot dip galvanized)		18
4	Safety valve of digester		3
5	Window with a searchlight, complete, disassembled	set	3
5.1	Inspection window RD300 (mounts and sealant included)	Ø300	6
5.2	Spotlight (mount system bundled) VISULUX UL50 -G -H	230V, 50W, IP65	6
6	Substrate pump to Separator with Frequency converters	30m3/hour N=11 kW	3
7	Separator	N=5,5 kW, Q=30 m³/h	3
7.1	Body		3
7.2	Substrate Supply Pipe 4 ''		3
7.3	Engine - Gearbox	N=5,5 kW	3
7.4	Frame		3
7.5	Screw		3
7.6	Sieve for filtration		3


Nº	Equipment	Characteristic	Q-ty
8	Submersible mixer (Receiving tank)	N=3.0 kW	1
8.1	Airtight motor gearbox		1
8.2	Hydraulic screw (wear-resistant steel)		1
8.3	Mixer control mechanism (high-quality structural galvanized steel)		1
8.4	Electric motor mount (high-quality structural galvanized steel)		1
8.5	Set of fasteners (coating - hot dip galvanized)		1
9	Filtrate pump	30 m3/hour N=11 kW	1
10	PVC external gas holder, complete, disassembled	V=800m³	1
10.1	Weather protection film	Ø12,6m	1
10.2	Gasholder film PELD methane permeation max.260 cm ³ /m ² *d*1 bar, 650 N/5cm biogas resistant		1
10.3	Air blower	16A, 0,5kW	1
10.4	Excess and minimum pressure valve		1
10.5	Dome level sensor		1
10.6	Mounting system		1
10.7	Accessories		1
11	Biogas cooling system	1600 m3/hour N=75,0 kW	2
12	Biogas compressor	Q=3100 m³/h H=150mBar N=36,0 kW	2
13	Desulphurization system	3 000 kg	3
13.1	Numbers of charcoal columns		3
14	Electromagnetic flow meter		1
15	Gas analyzer		1

Nº	Equipment	Characteristic	Q-ty
16	Flare	3100 m³/h	1
16.1	Compressor		1
16.2	Manual locking element		1
16.3	Deflagration fuse		1
16.4	On-site control cabinet		1
16.5	Auto ignition system		1
16.6	Auto Main Gas Solenoid Valve		1
17	Cogeneration power plant	2300 kW	3
18	The heat supply system	set	1
18.1	Circulation pump for supplying network water and electric boiler	G=7,8m ³ /h, H=6 m, Ne=0,37 kW, Dn40	1
18.2	Circulation pump of network supply water	G=0,74 m ³ /h, H=3m, Ne=0,04 kW, Dn15	1
18.3	Circulation pump for supplying network water to CHP	G=31 m ³ /h, H=8m, Ne=1,5 kW _T , Dn65	1
18.4	Propylene glycol feed pumping station for the heat supply system	G = 1.0 m ³ /h, H = 40 m, N = 0.775 kW,	1
18.5	Diaphragm expansion tank with volume V = 500L	P=10Bar, T=120°C, R1"	1
18.6	Propylene glycol storage tank with volume V = 300L with overflow line and float shut-off valve (kit)		1
18.7	Propylene glycol consumption meter for feeding the heat supply system of the biogas plant	DN15, G = 1.5 m ³ /h	1
18.8	Circulation pump for mains supply to the digester	G=11 m ³ /h, H=10m, Ne=0,75 kW, Dn50 ATEX EEx	1
20.9	Butterfly valve with el. drive	400V 3PH 50Hz	1
18.10	Three-way flanged control valve KVs6,3, Pn = 1.6MPa, DN20 with electric drive	U = 220V, N = 3.5 W, T = 150 s, 3-position	
18.11	Three-way flanged control valve KVs40, Pn = 1.6MPa, DN50 with electric drive	U = 220V, N = 3.5 W, T = 150 s, 3-position	
21	Automation with electrical equipment complete		1
21.1	Introductory switchgear VRU-1		1

Nº	Introductory switchgear VRU-2		1
21.2	Introductory switchgear VRU-3		1
21.3	Ventilation board for generator room SHVG-1		1
21.4	Ventilation board for generator room SHVG-2		1
21.5	Ventilation board for generator room SHVG-3		1
21.6	Ventilation board for generator room SHVG-3	SPA-380-08 (0-6m)	5
22	Sensors set		1
22.1	Pressure sensor (gas pressure)	0,025 bar	3
22.2	Pressure sensor (gas pressure)	0,4 bar	3
22.3	Pressure sensor (substrate level)	1 bar	3
22.4	Pressure sensor (substrate pressure)	2,5 bar	5
22.5	Pressure sensor (coolant pressure)	6 bar	12
22.6	Thermoconverter (gas)	Pt100	3
22.7	Thermoconverter (substrate in fermenters)	Pt100	6
22.8	Thermoconverter (heat carrier)	Pt100	12
22.9	Conductometric sensor		6
22.10	Conductometric sensor		1
22.11	Radar level sensor		2
22.12	Gas level sensor (gas holder)		1

APPENDICES





Raw biogas: 74083 Nm³/day
 (3087 Nm³/h)
 Methane (CH₄): 52 %
 Temperature: +48 °C
 Pressure: 0,5 mba
 Wet: 90-100%
 Density: 1,31kg/m³
 Weight: 97tonne
 H₂S: 1200 ppm

Raw biogas 74083 Nm³/day
 (3087 Nm³/h)
 52 % CH₄
 Temperature: +48 °C
 Pressure: 0,5 mba
 Wet: 90-100%
 H₂S: 1200 ppm

Biogas 74083Nm³/day
 52 % CH₄
 Temperature: +20 C
 Pressure: 0,5 mba
 Wet: 50%
 H₂S: 1200 ppm

Biogas 74083Nm³/day
 52 % CH₄
 Temperature: +40 C
 Pressure: 150 mba
 Wet: 50%
 H₂S: 1200 ppm

Biogas 74083Nm³/day
 52 % CH₄
 Temperature: +40C
 Pressure: 150 mba
 Wet: 50%
 H₂S: 5..10ppm


Biogas flare
 Flow rate 3920 m³/h

Legend main sensors

- FT Flow meter
- LCI Load Cell sensor
- LT Level sensor
- PT Pressure sensor
- TT Temperature sensor

Legend main pipelines


- TCS Substrate
- TCF Filtrate
- BG1 Biogas
- BG2 Biogas
- HS
- HS Heat system pipeline



Specification

N/Nº	Name	Q-y	N/Nº	Name	Q-y
1	Solid loader Nº1	1	7	Equipment room	1
1.1	Screws Nº1	3	8	Receiving tank	1
2	Solid loader Nº2	1	8.1	Submersible mixer	1
2.1	Screws Nº2	3	8.2	Substrate pump	1
3	Solid loader Nº3	1	9	Filtrate tank	1
3.1	Screws Nº3	3	9.1	Substrate (filtrate) pump	1
4	Digester Nº1	1	10	Separator platform	1
4.1	Vertical mixer Nº1	6	11	External gasholder	1
4.2	Safety valve Nº1	1	12	Gas treatment site	1
4.3	Inspection windows Nº1	2	12.1	Biogas cooling system	2
4.4	Gas flow meter Nº1	1	12.2	Biogas compressor	2
4.5	Digester cooling system Nº1	1	12.3	Desulphurization system	3
4.6	Digested substrat pump Nº1	1	12.4	Biogas analyzer	1
4.7	Separator Nº1	1	12.5	Biogas flow meter	1
5	Digester Nº2	1	13	Technical room	1
5.1	Vertical mixer Nº2	6	14	Generator room	1
5.2	Safety valve Nº2	1	14.1	CHP unit Nº1	1
5.3	Inspection windows Nº2	2	14.2	CHP unit Nº2	1
5.4	Gas flow meter Nº2	1	14.3	CHP unit Nº3	1
5.5	Digester cooling system Nº2	1	15	Biogas flare	1
5.6	Digested substrat pump Nº2	1			
5.7	Separator Nº2	1			
6	Digester Nº3	1			
6.1	Vertical mixer Nº3	6			
6.2	Safety valve Nº3	1			
6.3	Inspection windows Nº3	2			
6.4	Gas flow meter Nº3	1			
6.5	Digester cooling system Nº3	1			
6.6	Digested substrat pump Nº3	1			
6.7	Separator Nº3	1			

Plan



Legend of buildings and structures

N/№	Name	Note
1	Solid loader №1	
2	Solid loader №2	
3	Solid loader №3	
4	Digester №1	
5	Digester №2	
6	Digester №3	
7	Equipment room	
8	Receiving tank	
9	Filtrate tank	
10	Separator platform	
11	External gasholder	
12	Gas treatment site	
13	Technical room	
14	Generator room	
15	Spare parts warehouse	
16	Biogas flare	
17	Electric control room	(external design)
18	Water supply pump station	
19	Water storage tanks	
20	Waste water treatment	
21	Rainwater treatment facilities	
22	Lagoon	
23	Silo	

Appendix 4

Biogas plant					
Name equipment	Instal. Pow. (kW)	Q-y (pcs)	Total installed power (kW)	Working hours per day	Consumption kWh per day
Loader V=50 m ³	23,0	3	69,0	7,0	483,0
Screw set.	24,0	3	72,0	7,0	504,0
Digester Vertical agitator	15,0	18	270,0	18,0	4860,0
Submersible agitator in receiving tank	2,0	1	2,0	12,0	24,0
Biogas cooling system	75,0	2	150,0	24,0	3600,0
Biogas compressor	36,0	1	36,0	24,0	864,0
Separator	7,5	3	22,5	9,0	202,5
Substrate feed pump	11,0	1	11,0	3,0	33,0
Substrate pump to separator	11,0	3	33,0	9,0	297,0
Filtrate pump	11,0	1	11,0	3,0	33,0
Cogenerator self consumption	21,0	3	63,0	24,0	1512,0
Air compressor for gasholder lock	1,5	1	1,5	1,0	1,5
Air blower for double membrane	1,0	1	1,0	24,0	24,0
Digester cooling system	4,0	3	12,0	at t>55°C	
Circulation pump for supplying heat carrier to the digester	0,75	3	2,3	24,0	54,0
Circulation pump for supplying network water to the digester cooling system	2,0	1	2,0	24,0	48,0
Circulating pump feeding hot water at technical building	0,37	1	0,4	only ambient temp +15°C	
Propylene glycol pump station	0,8	1	0,8	0,5	0,4
Water supply pump station (drinking water)	0,75	1	0,8	3,0	2,3
Drinage pump	0,37	1	0,4	0,5	0,2
Lighting of the biogas plant territory	1,0	1	1,0	8,0	8,0
Spot light for digesters inspection windows	0,1	1	0,1	0,5	0,0
Working lighting of switchboard	0,1	1	0,1	0,5	0,1
Cogenerators self-consumption	21,0	3	63,0	24,0	1512,0
Total installed power, kW			825		
Total consumed electric energy, kWh per day					14063
Total consumed power, kW					586

Equipment price

Pos.	Description	Quantity	Unit Price, EUR	Total Price, EUR
1	Solid feeder (dosing buffer machine)	3	112 400,00	337 200,00
2	Screw conveyor	3	108 000,00	324 000,00
3	Digester vertical mixer N=15kW	18	48 200,00	867 600,00
4	External gasholder V=870m3	1	76 600,00	76 600,00
5	Over- and under pressure safeguard	3	4 100,00	12 300,00
6	Substrate separation unit 5,5kW	3	44 400,00	133 200,00
7	Substrate supply pump to separator unit	3	18 500,00	55 500,00
8	Submersible mixer with guiding unit for receiving tank 3 kW	1	8 000,00	8 000,00
9	Filtrate supply pump	1	18 500,00	18 500,00
10	Biogas burner	1	144 200,00	144 200,00
11	Biogas chiller (Biogas cooling system)	2	89 000,00	178 000,00
12	Desulphurization column with active coal	2	48 500,00	97 000,00
13	Biogas blower	1	31 200,00	31 200,00
14	Gas conditioning unit	1	16 800,00	16 800,00
15	Heat supply station	1	52 900,00	52 900,00
16	Motorized valves (set)	13	4 300,00	55 900,00
17	Automatic with electric equipment	1	290 600,00	290 600,00
18	Sensors (set)	1	47 700,00	47 700,00
19	Water supply and canalization system	1	41 800,00	41 800,00
20	Dry-cooler (Substrate cooling system for fermenter)	3	11 700,00	35 100,00
21	Biogas analyzer (CH4, CO2, H2S)	1	24 900,00	24 900,00
22	Sight glasses/viewing windows with projector	3	3 800,00	11 400,00
23	Substrate supply pump	1	18 500,00	18 500,00
24	Frame for pos.3	18	5 800,00	104 400,00
TOTAL: [DAP (Incoterms 2010): Ruse, Bulgaria]:				2 983 300,00

Price

Name	Price (DAP any place in EU)
➤ Project documentation	89 000 Euro
➤ Start-up and training	47 000 Euro
➤ Supervision and adjustment	47 000 Euro
➤ Living and travel expenses*	47 320 Euro
➤ Equipment	2 983 300 Euro
➤ Cogeneration power plants MWM Caterpillar 2300kW el. x 3	1 908 000 Euro
➤ Construction and installation**	3 000 000 Euro
Total	8 121 620 Euro

* Living and travel expenses:

During supervision:

8 visits x 7 days, airtickets 700 EUR x 8, hotel 5 days x 8 visits x 120 EUR, daily exp.
54 days x 120 EUR = 17 120 EUR

During startup and training:

1 visit x 60 days x 2 specialists, airtickets 700 x 2, hotel 120 x 2 x 60, daily exp 60 x
120 x 2 = 30 200 EUR

TOTAL 47 320 EUR

**** INCLUDES** Excavation 1,5 m, concrete reactor, technical building, concrete tanks, concrete foundations, steel structures, reactor thermal insulation, gas pipes, substrate pipes, cables, construction machinery lease, equipment installation
Doesn't include maize silage storages 150 000 m³ (2 million EUR) or lagoons 10 000 m³ (150 000 EUR)

Implementation terms and payment

Months	1	2	3	4	5	6	7	8	9	10	11	12
Project documentation	50%	50%										
Equipment supply	30%		20%	20%		10%						
CHP unit	30%					70%						
Construction												
Supervision	50%				50%							
Plant start-up									50%		50%	

Contracts

Project implementation is executed simultaneously under several contracts

- Engineering contract
- Equipment supply contract
- Supervision contract
- Start-up and training contract

ZORG BIOGAS

Business center "Twin Yards"
Walter-Gropius-Straße 23,
DE-80807, München, Germany

Mob. +49 1511 457 29 45 (WhatsApp, Viber, Telegram)

igor.reddikh@zorg-biogas.com
www.zorg-biogas.com